



BRICK NAME(S)	Parliament, Weathered Parliament, Vintage Stock
BRICK TYPE	Through colour clay handmade brick, some variants (Weathered Parliament and Vintage Stock) may have a non-permanent tinted exterior surface, this is an artificial weathering/aging tint and is not meant to be permanent.
SPECIFICATION	Manufactured to AS/NZS 4455 and BS EN 771-1:2011.
SIZE*	Nominal 65 x 215 x 102.5mm.
DIMENSIONAL TOLERANCE	DW3 size classification, +/- 5mm 1 sigma standard deviation from the nominal size (n=20) is to be expected. These are handmade bricks, if you are after high degrees of dimensional tolerance handmade bricks are not for you.
COMPRESSIVE STRENGTH	> 10 N/MM2
WATER ABSORPTION	Mean - 14%
SOLUBLE SALT CLASSIFICATION	S2
BULK DENSITY	1500 kg/m
PACKAGING	Shrink wrapped on wooden pallets in packs of <ul style="list-style-type: none">• 648 bricks to pallet.
PACK SIZE	L x W x H 1100 x 1100 x 1100mm Approx.
PACK WEIGHT	1.5 to 1.6 Tonnes Approx.
USAGE	Always mix from several packs.
DURABILITY	General Purpose Building Brick (AS/NZS 4455) F2 BS EN771-1:2011
PERFORMANCE	<ul style="list-style-type: none">• The recommendations of good practice made in the relevant Think Brick guides regarding design and workmanship must be fully observed. Liability cannot be accepted for the performance of the product if used outside our recommendations.• Guidance on the use of these bricks in specific situations is readily available from us.

*Individual bricks may vary dimensionally; this is a natural characteristic of fired clay bricks and is catered for in the relevant Australian, New Zealand and European Standards.
info@elephantbrickco.com.au