



BRICK NAME(S)	Federation Banded Wirecuts, Reclamation Federation Clinkers.
BRICK TYPE	Through colour clay machine made brick with fired oxide surface colourings.
SPECIFICATION	Manufactured to AS/NZS 4455 and BS EN 771-1:2011.
SIZE*	Nominal 76 x 230 x 110mm. Nominal 65 x 215 x 105mm. Nominal 65 x 215 x 16mm (cut slip).
DIMENSIONAL TOLERANCE	DW3 size classification, +/- 5mm 1 sigma standard deviation from the nominal size (n=20) is to be expected.
COMPRESSIVE STRENGTH	> 10 MPa
WATER ABSORPTION	Mean - 10%
SOLUBLE SALT CLASSIFICATION	S2
BULK DENSITY	1500 kg/m
PACKAGING	Shrink wrapped on wooden pallets.
PACK SIZE	L x W x H 1100 x 1100 x 1100mm Approx.
PACK WEIGHT	1.5 to 1.6 Tonnes Approx.
USAGE	Always mix from several packs.
DURABILITY	General Purpose Building Brick (AS/NZS 4455) F2 BS EN771-1:2011

PERFORMANCE

- The recommendations of good practice made in the relevant Think Brick guides regarding design and workmanship must be fully observed. Liability cannot be accepted for the performance of the product if used outside our recommendations.
- Guidance on the use of these bricks in specific situations is readily available from us.