



BRICK NAME(S)	Pale Sanded Grey, Roman Pale Sanded Grey.
BRICK TYPE	Handmade brick with grey exterior.
SPECIFICATION	Manufactured to AS/NZS 4455 and BS EN 771-1:2011.
SIZE*	Nominal 50 x 330 x 108mm, Nominal 65 x 215 x 105mm.
DIMENSIONAL TOLERANCE	DPB3 size classification, +/- 2mm 1 sigma standard deviation from the nominal size (n=20) is to be expected.
COMPRESSIVE STRENGTH	Mean – 10.5 N/MM ²
WATER ABSORPTION	Mean - 13%
SOLUBLE SALT CLASSIFICATION	S2
BULK DENSITY	1500 kg/m
PACKAGING	Shrink wrapped on wooden pallets in packs of <ul style="list-style-type: none">• 486 bricks to pallet.• 648 bricks to pallet
PACK SIZE	L x W x H 1100 x 1100 x 1100mm Approx.
PACK WEIGHT	1.5 to 1.6 Tonnes Approx.
USAGE	Always mix from several packs.
DURABILITY	General Purpose Building Brick (AS/NZS 4455) F2 BS EN771-1:2011
PERFORMANCE	<ul style="list-style-type: none">• The recommendations of good practice made in the relevant Think Brick guides regarding design and workmanship must be fully observed. Liability cannot be accepted for the performance of the product if used outside our recommendations.• Guidance on the use of these bricks in specific situations is readily available from us.

*Individual bricks may vary dimensionally; this is a natural characteristic of fired clay bricks and is catered for in the relevant Australian, New Zealand and European Standards.
info@elephantbrickco.com.au